

Product Technical Statement

Product Description:

Hardie™ Ceramic Tile Underlay is available in a 6mm thickness.

Scope of Use:

Hardie™ Ceramic Tile Underlay is suitable for use as a substrate over internal flooring to lay tiles, heavy grade vinyl or cork over for use in dry or wet area applications.

Limitations:

Hardie™ Ceramic Tile Underlay must not be used in following situations:

- In external deck applications
- Directly over concrete

Compliance with the NZBC:

The following clauses of the NZBC are applicable to Hardie™ Ceramic Tile Underlay and it complies with these requirements as explained below.

Durability - B2: Hardie™ Ceramic Tile Underlay is manufactured in accordance with AS/NZS 2908.2 and meets the durability performance requirements of Clause B2.3.1 (b) and B2.3.2.

Hazardous Building Materials - F2: Hardie™ Ceramic Tile Underlay complies with the requirements of Clause F2.3.1 and will not present a health hazard when handled as per its installation manual.

Installation:

Hardie™ Ceramic Tile Underlay must be installed in accordance with the Flooring Installation Manual by James Hardie. The information and details are available online at www.jameshardie.co.nz or Ask James Hardie™ at 0800 808 868 for further information.

Warranty:

Hardie™ Ceramic Tile Underlay has a product warranty of 15 years when installed and maintained as per the current installation manual.

Hardie™ Ceramic Tile Underlay is not subject to a warning or ban under section 26 of the Building Act.

Hardie™ Ceramic Tile Underlay is manufactured in Australia.